



REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.			
C3	依TN1807190131新增电镀规格	18.07.19		LINEAR	ANGLES	1:1							
C4	依ECN20220725183新增规格	22.07.25	0.0 ± 0.25	X° REF ± 6°	APPROVED		23.11.06	11251TOP-XX-D-NK	ENDE05				
C5	PBJOA202212150002	23.01.04	0.00 ± 0.15	X° ± 3°	DESIGNER								
C6	YB202308100001	23.11.06	SIZE: A4	0.000 ± 0.08	X° X' ± 2°	DRAWN	Fau	TITLE	MX1.25 端子	REV	C6	SHEET	1/2

1 2 3 4 5 6 7 8

Part No	Wire Range	Insulation O.D	Material	Finish	Qty/reel
11251TOP-2E-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni 30u"Min Tin 100u"Min	15,000pcs
11251TOP-3E-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni 30u"Min Tin 80u"Min	15,000pcs
11251TOP-5A-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:Gold flash(测点1)	15,000pcs
11251TOP-5B-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:2u"Min(测点1)	15,000pcs
11251TOP-5C-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:3u"Min(测点1)	15,000pcs
11251TOP-5D-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:4u"Min(测点1)	15,000pcs
11251TOP-5E-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:5u"Min(测点1)	15,000pcs
11251TOP-5F-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:10u"Min(测点1)	15,000pcs
11251TOP-5G-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:15u"Min(测点1)	15,000pcs
11251TOP-5H-D-NK	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:30u"Min(测点2)	15,000pcs
11251TOP-2E-D-NK-DP	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni 30u"Min Tin 100u"Min	15,000pcs
11251TOP-5A-D-NK-DP	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:Gold flash(测点1)	15,000pcs
11251TOP-5B-D-NK-DP	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:2u"Min(测点1)	15,000pcs
11251TOP-5C-D-NK-DP	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:3u"Min(测点1)	15,000pcs
11251TOP-5D-D-NK-DP	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:4u"Min(测点1)	15,000pcs
11251TOP-5E-D-NK-DP	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:5u"Min(测点1)	15,000pcs
11251TOP-5F-D-NK-DP	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:10u"Min(测点1)	15,000pcs
11251TOP-5G-D-NK-DP	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:15u"Min(测点1)	15,000pcs
11251TOP-5H-D-NK-DP	AWG#28~#32	1.00mm(Max)	Phosphor Bronze	Ni:50u"Min,Au:30u"Min(测点2)	15,000pcs

C6



Note: 11251TOP-XX-D-NK

Finish(Measuring point) NK: 无印字
表示: D TYPE
 5A--Gold flash 5B--2u" 5C--3u" 5D--4u"
 5E--5u" 5F--10u" 5G--15u" 5H--30u"
 2E--Tin-plated 3E--Matte Tin-plated



REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE 1:1	NAME	DATE	PART NO.	DWG NO.	
C3	依TN1807190131新增电镀规格	18.07.19			LINEAR	ANGLES	APPROVED		23.11.06	11251TOP-XX-D-NK	
C4	依ECN20220725183新增规格	22.07.25	0.0±0.25		X° REF±6°	DESIGNER	TITLE				
C5	PBJ0A202212150002	23.01.04	UNIT: MM	0.00±0.15	X° ±3°	DRAWN	Fau	23.11.06	MX1.25 端子		
C6	YB202308100001	23.11.06	SIZE: A4	0.000±0.08	X° X' ±2°						

REV C6 SHEET 2/2

1 2 3 4 5 6 7 8