



- 11251W00-NPX-XX-HF  
 ① ② ③④ ⑤ ⑥
- ① Series No.
  - ② W90 : Side Contact  
W00 : Up Contact
  - ③ No. of Circuits
  - ④ X : Product color(A--Y)  
Blank : Natural type
  - ⑤ 3E : Matter Tin-plated  
5A : Gold Flash  
5G : Gold-plated 15u"
  - ⑥ HF :Halogen Free

Circuits Part No	Dimensions	
	A	B
2P		4.35
3P	2.50	5.60
4P	3.75	6.85
5P	5.00	8.10
6P	6.25	9.35
7P	7.50	10.60
8P	8.75	11.85
9P	10.00	13.10
10P	11.25	14.35
11P	12.50	15.60
12P	13.75	16.85
13P	15.00	18.10
14P	16.25	19.35
15P	17.50	20.60
20P	23.75	26.85

Specifications:  
 Rated Voltage : 125V AC/DC  
 Rated Current : 1A AC,DC  
 Withstand Voltage : 250V AC/minute  
 Contact Resistance : 20mΩ(MAX.)  
 Insulation Resistance : 100MΩ(MIN.)  
 Temperature Range : -40°C~+85°C  
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Part No.	Material	Color	Pin Material
11251W00-NP	High temperature plastic,UL94V-0	Natural(Beige)	Phosphor Bronze/Tin-plated
11251W00-NPE	High temperature plastic,UL94V-0	Yellow	Phosphor Bronze/Tin-plated
11251W00-NP-HF	High temperature plastic,UL94V-0	Natural(Beige)	Phosphor Bronze/Tin-plated
11251W00-NPC-HF	High temperature plastic,UL94V-0	Red	Phosphor Bronze/Tin-plated
11251W00-NP-3E-HF	High temperature plastic,UL94V-0	Natural(Beige)	Phosphor Bronze/Matter Tin-plated
11251W00-NP-5A	High temperature plastic,UL94V-0	Natural(Beige)	Phosphor Bronze/Gold Flash
11251W00-NP-5G-HF	High temperature plastic,UL94V-0	Natural(Beige)	Phosphor Bronze/Gold-plated 15u"
11251W00-NPA-5G-HF	High temperature plastic,UL94V-0	Black	Phosphor Bronze/Gold-plated 15u"

REV.	REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE	NAME	DATE	PART NO.	DWG NO.
C0		换图框发行	2009. 11. 25	LINEAR	1:1			11251W00-NPX-XX	ENDE05
C4		WN2011120327	2020. 10. 28	0.0±0.25	APPROVED	Ym	24.04.29	Molex 1.25mm PITCH DIP WAFER	JCTC®
C5		YB20230210002	2023. 03. 07	0.00±0.15	DESIGNER	SP PERB	24.04.29		
C6		YB202312260001	2024. 04. 29	0.000±0.08	DRAWN	Noah	24. 04. 29		
				X° REF±6°					
				X° ±3°					
				X° X' ±2°					

REV	C6	SHEET	1/1
-----	----	-------	-----