



Dimensional Ordering Information:

Circuits Part No	Dimensions	
	A	B
2P	4.35	4.35
3P	2.50	5.60
4P	3.75	6.85
5P	5.00	8.10
6P	6.25	9.35
7P	7.50	10.60
8P	8.75	11.85
9P	10.00	13.10
10P	11.25	14.35
11P	12.50	15.60
12P	13.75	16.85
13P	15.00	18.10
14P	16.25	19.35
15P	17.50	20.60
20P	23.75	26.85

Specifications:  
 Rated Voltage : 125V AC/DC  
 Rated Current : 1A AC,DC  
 Withstand Voltage : 250V AC/minute  
 Contact Resistance : 20mΩ(MAX.)  
 Insulation Resistance : 100MΩ(MIN.)  
 Temperature Range : -40°C~+85°C  
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

- 11251W90-NP-R  
 ① ② ③ ④  
 ① Series No.  
 ② W90 : Side Contact  
 W00 : Up Contact  
 ③ No. of Circuits  
 ④ R: Tape & Reel



Part No.	Material	Color	Pin Material
11251W90-NP-R	High temperature plastic,UL94V-0	Natural(Beige)	Phosphor Bronze/Tin-plated

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.	JCTC®			
AO	The new version file were released	2023.06.09	LINEAR	ANGLES	1:1			11251W90-NP-R	ENDE05				
			0.0±0.25	X° REF±6°	APPROVED	<i>mm</i>	23.12.12						
			UNIT: MM	0.00±0.15	X° ±3°	DESIGNER	<i>Noah</i>	TITLE					
			SIZE: A4	0.000±0.08	X° X' ±2°	DRAWN	SP Peng	Molex 1.25mm PITCH DIP WAFER					
										REV	AO	SHEET	1/2

