



Circuits No.	Dimensions	
	A	B
2x2P	4.50	2.00
2x3P	6.50	4.00
2x4P	8.50	6.00
2x5P	10.50	8.00
2x6P	12.50	10.00
2x7P	14.50	12.00
2x8P	16.50	14.00
2x9P	18.50	16.00
2x10P	20.50	18.00
2x11P	22.50	20.00
2x12P	24.50	22.00
2x13P	26.50	24.00
2x14P	28.50	26.00
2x15P	30.50	28.00
2x16P	32.50	30.00
2x17P	34.50	32.00
2x18P	36.50	34.00
2x19P	38.50	36.00
2x20P	40.50	38.00

Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 20mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25℃~+85℃
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

12002H00-2xNPA-L-HF
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② H90 : Side Contact
- H00 : Up Contact
- ③ No. of Circuits
- ④ A : Black
- ⑤ L : Mount type
- ⑥ HF : Halogen Free



Part No.	Material	Color
12002H00-2xNP-L	Nylon 66,UL94V-0	本色
12002H00-2xNP-L-HF	Nylon 66,UL94V-0	本色无卤
12002H00-2xNPA-L-HF	Nylon 66,UL94V-0	黑色无卤

REV.	REVISION RECORD	DATE	UNIT: MM	SIZE: A4	GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	PART. NO:	DWG. NO:	 JCTC ® TERMINAL&CONNECTORS
C0	新图面发行	09.11.25			LINEAR				12002H00-2XNPX-L-XX	ENDE05	
C1	HN2003030027	20.03.03			0.0±0.25	ANGLES					
					X° REF±6°						
					0.00±0.15	X° ±3°	DESIGNER	张振坤	20.03.03	TITLE:	
					0.000±0.08	X° X' ±2°	DRAWN	张振坤	20.03.03	PHD 双排带扣 2.00mm PITCH	
											REV: C1 SHEET: 1/1