



PART NO.	Dimensions	
	A	B
2x2	--	6.00
2x3	4.00	8.00
2x4	6.00	10.00
2x5	8.00	12.00
2x6	10.00	14.00
2x7	12.00	16.00
2x8	14.00	18.00
2x9	16.00	20.00
2x10	18.00	22.00
2x11	20.00	24.00
2x12	22.00	26.00
2x13	24.00	28.00
2x14	26.00	30.00
2x15	28.00	32.00
2x16	30.00	34.00
2x17	32.00	36.00
2x18	34.00	38.00
2x19	36.00	40.00
2x20	38.00	42.00

Specifications:  
 Rated Voltage : 250V AC/DC  
 Rated Current : 3A AC,DC  
 Withstand Voltage : 800V AC/minute  
 Contact Resistance : 10mΩ(MAX.)  
 Insulation Resistance : 1000MΩ(MIN.)  
 Temperature Range : -25°C~+85°C  
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

12002W00-2XNXP-P1-HF  
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② W90 : Side Contact  
W00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color(A--Y)  
Blank : Natural type
- ⑤ P1 : P1 Type
- ⑥ HF : Halogen Free



Part No.	Material	Color	PIN Material
12002W00-2XNXP-P1-HF	Nylon 66,UL94V-0	Natural(White)	Brass/Tin-plated
12002W00-2XNPA-P1-HF	Nylon 66,UL94V-0	Black	Brass/Tin-plated

REV.	REVISION RECORD	DATE
A0	新图面发行	19.08.29



GENERAL TOLERANCES		SCALE:	NAME	DATE
LINEAR	ANGLES	1:1	张振坤	19.11.27
0.0±0.25	X° REF±6°	APPROVED		
0.00±0.15	X° ±3°	DESIGNER		
SIZE: A4	0.000±0.08	0.00±0.15	X° X'±2°	DRAWN
		0.000±0.08	X° X'±2°	张振坤

**JCTC**® 胜蓝科技股份有限公司  
 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司

TITLE: PHD 双排 2.00mm PITCH WAFER

PART NO:	12002W00-2XNXP-P1-XX	
DWG NO:	ENDE05	
REV:	A0	SHEET: 1/1