



Note: 13962TOB-2E

Finish \_\_\_\_\_  
 2E--Stamping before Tin-plated  
 0A--Stamping before Gold-flash

Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
13962TOB-2E	AWG #18~#22	2.80mm(max)	Brass	Ni 30u"Min. Tin-plated 60u"Min.	3,000 pcs
13962TOB-0A	AWG #18~#22	2.80mm(max)	Brass	Ni 30u"Min. plated Gold-flash	3,000 pcs

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.	 <b>JCTC</b> <sup>®</sup> TERMINAL&CONNECTORS
C2	增加C角	2013.11.11		LINEAR	ANGLES	1:1					
C3	修改每盘包装数量	2014.07.29	0.0±0.25	X° REF±6°	APPROVED	<i>Nelson</i>	23.03.02	13962TOB-2E	ENDE05		
C4	变更公司名称	2017.03.07	0.00±0.15	X° ±3°	DESIGNER	<i>WU</i>	23.03.02	TITLE			
C5	依据YB20230308004新增规格	2023.03.08	SIZE: M4	0.000±0.08	X° X' ±2°	DRAWN	Hui	2023.03.02	3.96mm PITCH Terminal		

REV C5 SHEET 1/1